


LABCO Ltd




83 Laroche #103, Repentigny, Qc, J6A 7M3 Tel: (450) 581-7589 Fax: (450) 581-8463

Garantie à Vie
Lifetime Warranty



CRS24-2

Relais de contrôle sensible
24VDC 2 amps
Sensible control relay



Spécifications

- 2 voltages disponibles:
 - CRS12-2: 12VCC, bobine de 960 ohms
 - CRS24-2: 24VCC, bobine de 2880 ohms
- Montage sur circuit imprimé
- Indicateur d'état de type DEL
- Diode de protection contre les renversements de polarités et le courant inverse du relais
- Contact DPDT
- Courant maximal: 2A CC/CA
- Voltage maximal: 250VCA 220VCC
- Puissance maximale: 60 watts ou 125VA
- Installation facilitée par l'utilisation de ruban adhésif inclus
- Dimensions:

- Hauteur:	0.550"	(14mm)
- Largeur:	1.800"	(45mm)
- Longueur:	1.300"	(33mm)

Specifications

- 2 available voltages:
 - CRS12-2: 12VDC, 960 ohm coil
 - CRS24-2: 24VDC, 2880 ohm coil
- PCB type
- LED status indicator
- Polarity diode
- Surge diode
- DPDT contact
- Max. switching current: 2A AC/DC
- Max. switching voltage: 250VAC 220VDC
- Maximum power: 60 watts or 125VA
- Adhesive foam mounting tape
- Dimensions:

- Height:	0.550"	(14mm)
- Width:	1.800"	(45mm)
- Length:	1.300"	(33mm)

LABCO Ltd 83 Laroche #103, Repentigny, Qc, J6A 7M3. Tel: (450) 581-7589 Fax: (450) 581-8463