

SUPER THERMAL GREASE II

8616

# Safety Data Sheet

## Section 1: Identification

### Product Identifier and Other Means of Identification

**Product Name:** Super Thermal Grease II**SDS Code:** 8616**Related Part #** 8616-4G, 8616-3ML, 8616-25ML, 8616-85ML, 8616-1P, 8616-1G

### Recommended Use and Restriction on Use

**Use:** Thermal interface grease for improving heat flow between the CPU and heat sink**Uses Advised Against:** Not applicable

### Details of Manufacturer or Importer

**Manufacturer**MG Chemicals  
1210 Corporate Drive  
Burlington, Ontario L7L 5R6  
CANADAMG Chemicals (Head Office)  
9347-193 Street  
Surrey, British Columbia V4N 4E7  
CANADA**☎** +1-800-340-0772  
**Fax** +1-800-340-0773  
**E-mail** support@mgchemicals.com  
**Web** www.mgchemicals.com**☎** +1-905-331-1396  
**Fax** +1-905-331-2682  
**E-mail** info@mgchemicals.com**E-MAIL** (Competent Person): [sds@mgchemicals.com](mailto:sds@mgchemicals.com)

### Emergency Phone Number


**For hazardous material incidents ONLY**—leaks, spills, fires, exposures or accidentsUSA or CANADA: Call CHEMTREC ☎: **+1-800-424-9300****For emergencies involving dangerous goods;** Collect 24/7CANADA: Call CANUTEC ☎: **+1-613-996-6666** or **\*666** on cellular phones

**SUPER THERMAL GREASE II**
**8616**
**Section 2: Hazard(s) Identification**
**Classification of Hazardous Chemical**
**GHS Categories**

Criteria	Category	Signal Word	Pictograms
Hazardous to the Aquatic Environment Chronic	1	Warning	Environment

*Note:* The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity), which is opposite to HMIS and NFPA conventions. Severity category rankings do not allow comparisons between classes.

**Label Elements**

<b>Signal Word</b>	<b>WARNING</b>
<b>Pictograms</b>	<b>Hazard Statements</b>
	H410: Very toxic to aquatic life with long lasting effects
<b>Prevention</b>	<b>Precautionary Statements</b>
P273	Avoid release to the environment.
<b>Response</b>	<b>Precautionary Statements</b>
P391	Collect Spillage.
<b>Storage</b>	<b>Precautionary Statements</b>
<i>none</i>	<i>none</i>
<b>Disposal</b>	<b>Precautionary Statements</b>
P501	Dispose of contents/container in accordance to local/regional/national/international regulations.

**Hazards Not Otherwise Classified**

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
None	None	None	None

**SUPER THERMAL GREASE II**

**8616**

**Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
1344-28-1	aluminum oxide	42%
1314-13-2	zinc oxide	37%

**Section 4: First Aid Measures**

*Exposure Condition*

*GHS Code: Precautionary Statement*

**IF IN EYES** P305 + P351 + P338, P337 + P313

**Immediate Symptoms** *redness, mild irritation, pain*

**Response** Rinse cautiously with water for 15 minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.

**IF ON SKIN** P302 + P352, P332 + P313

**Immediate Symptoms** *mild irritation*

**Response** Wash with plenty of water.  
If irritation occurs: Get medical advice/attention.

**IF SWALLOWED** P301 + P330, P331

**Immediate Symptoms** *Low toxicity—without known symptoms or adverse effects*

**Response** Rinse mouth. Do NOT induce vomiting.

**IF INHALED** P304 + P340, P312

**Immediate Symptoms** *Low toxicity—without known symptoms or adverse effects*

**Response** Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.  
If feeling unwell: Call a POISON CENTRE/doctor.

**SUPER THERMAL GREASE II****8616****Section 5: Fire Fighting Measures**

<b>Extinguishing Media</b>	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
<b>Specific Hazards</b>	<p>In case of fire, this product can release zinc and aluminum oxide fumes. Zinc and aluminum oxide fumes exposure may lead to a metal fume fever. The symptoms of metal fume fever may occur 4 to 12 hours after initial exposure.</p> <p>Prevent fire-fighting wash from entering waterway or sewer system.</p>
<b>Combustion Products</b>	Produces carbon oxides (CO,CO <sub>2</sub> ), zinc oxides (ZnO), and aluminum oxides (Al <sub>2</sub> O <sub>3</sub> ).
<b>Fire-Fighter</b>	Wear self-contained breathing apparatus and full fire-fighting turnout gear.

**Section 6: Accidental Release Measures**

<b>Personal Protection</b>	See personal protection equipment in Section 8.
<b>Precautions for Response</b>	Remove or keep away all sources of extreme heat. Avoid breathing fumes.
<b>Environmental Precautions</b>	Avoid release to the environment. Prevent spill from entering drains and waterways.
<b>Containment Methods</b>	Not applicable—not readily flowable
<b>Cleaning Methods</b>	Collect grease in a sealable, oil-resistant container. Wipe up further residue with paper towel and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue.
<b>Disposal Methods</b>	Dispose of spill waste according to Section 13.

**SUPER THERMAL GREASE II**

**8616**

**Section 7: Handling and Storage**

- Prevention** Keep out of reach of children.  
 Keep away all sources of extreme heat. Avoid breathing fumes.  
 Avoid release to the environment.
- Handling** Wear protective gloves/eye protection.  
 Wash hands thoroughly after handling.  
 Collect spillage.
- Storage** **RECOMMENDATION:** Keep in a dry and clean area, away from incompatible substances.

**Section 8: Exposure Controls/Personal Protection**

**Substances with Occupational Exposure Limit Values**

Chemical Name	Country or Vendor	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
aluminum metal and insoluble compounds <sup>a)</sup>	ACGIH	1 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	15 mg/m <sup>3</sup>	Not established
	Canada AB	10 mg/m <sup>3</sup>	Not established
	Canada BC	1 mg/m <sup>3</sup>	Not established
	Canada ON	1 mg/m <sup>3</sup>	Not established
	Canada QC	10 mg/m <sup>3</sup>	Not established
zinc oxide (dust/mist)	ACGIH	2 mg/m <sup>3</sup>	Not established
	U.S.A. OSHA PEL	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Canada AB	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Canada BC	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Canada ON	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Canada QC	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
fumes dust	Canada QC	2 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
	Canada QC	10 mg/m <sup>3</sup>	Not established

*Note:* Ingredients are listed in descending weight contribution order (from greatest to least). The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the RTECS<sup>2</sup> database and data from suppliers' SDSs were also consulted. Short term exposure limits (STEL) are for 15 min and long term permissible exposure limits (PEL) for 8 h.

*Section continued on the next page*

**SUPER THERMAL GREASE II****8616****Engineering Controls****Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Because zinc oxide and aluminum oxide are inextricably bound to the adhesive mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

**Personal Protective Equipment****Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

**Recommendation:** Ensure that glasses have side shields for lateral protection.

**Skin Protection**

For likely contacts, use of protective butyl rubber or other chemically resistant gloves.

For incidental contacts, use nitrile or other chemically resistant gloves.

**Respiratory Protection**

If exposed to thermal degradation products from extreme heat or combustion conditions, wear a NIOSH approved self-contained breathing apparatus (SCBA) or supplied air respirator.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

**General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

**SUPER THERMAL GREASE II**
**8616**
**Section 9: Physical and Chemical Properties**

<b>Physical State</b>	Solid	<b>Lower Flammability Limit</b>	Not applicable
<b>Appearance</b>	White, grease	<b>Upper Flammability Limit</b>	Not applicable
<b>Odor</b>	Odorless	<b>Vapor Pressure @20 °C</b>	Not available
<b>Odor Threshold</b>	Not available	<b>Vapor Density</b>	Not available
<b>pH</b>	Not available	<b>Specific Gravity @25 °C</b>	2.69
<b>Freezing/Melting Point</b>	Not available	<b>Solubility in Water</b>	Insoluble
<b>Boiling Point</b>	Not available	<b>Partition Coefficient</b>	Not available
<b>Flash Point <sup>a)</sup></b>	290 °C [554 °F]	<b>Auto-ignition Temperature</b>	Not available
<b>Evaporation Rate</b>	Not available	<b>Decomposition Temperature</b>	Not available
<b>Flammability (solid, gas)</b>	Not available	<b>Viscosity @40 °C</b>	>20.5 mm <sup>2</sup> /s

a) based on synthetic oil

**Section 10: Stability and Reactivity**

<b>Reactivity</b>	When the product is exposed to very high heat such as welding or when mechanically aerosolized, this may cause harmful zinc oxide and aluminum oxide fumes. These fumes can cause metal fume fever. The symptoms of metal fume fever may occur 4 to 12 hours after initial exposure.
<b>Chemical Stability</b>	Chemically stable at normal temperatures and pressures
<b>Conditions to Avoid</b>	Very high heat (such as soldering or welding) and incompatible substances.
<b>Incompatibilities</b>	Halogenated compounds, strong oxidizing agents, strong acids, strong bases
<b>Polymerization</b>	Will not occur
<b>Decomposition</b>	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5.

**SUPER THERMAL GREASE II**

**8616**

**Section 11: Toxicological Information**

**Routes of Exposure**

Eye contact, Skin contact, Inhalation

**Symptoms Summary**

**Eyes** May cause redness, a mild eye irritation, or pain. The aluminum oxide and zinc oxide is mechanically abrasive.

**Skin** May cause a mild skin irritation.

**Inhalation** No symptoms or adverse effects anticipated under normal use.  
When heated to extreme temperatures, fumes from product can cause metal fume fever and respiratory irritation.

**Ingestion** Low toxicity—without known symptoms or adverse effects

**Chronic** Not applicable

**Acute Toxicity (Lethal Exposure Concentrations)**

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
aluminum oxide	Not available	Not available	Not available
zinc oxide	7 950 mg/kg Rat	Not established	2 500 mg/m <sup>3</sup> mouse

*Note:* Toxicity data from the RTECS<sup>2</sup> and ECHA were consulted. The data from supplier (M)SDS were also consulted.

**Other Toxicological Effects**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** May cause mild eye irritation. Contains mechanically abrasive particles.

**Sensitization** (allergic reactions) Based on available data, the classification criteria are not met.

**Carcinogenicity** (risk of cancer) Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP

**Mutagenicity** (risk of heritable genetic effects) Based on available data, the classification criteria are not met.

*Section continued on the next page*



**SUPER THERMAL GREASE II****8616****Reproductive Toxicity**

(risk to sex functions)

Based on available data,  
the classification criteria are not met.**Teratogenicity**

(risk of fetus malformation)

Based on available data,  
the classification criteria are not met.**STOT-single exposure**Based on available data,  
the classification criteria are not met.**STOT-repeated exposure**Based on available data,  
the classification criteria are not met.**Aspiration hazard**Based on available data, the classification criteria are  
not met. There are no category 1 components, and the  
kinematic viscosity is  $>20.5 \text{ mm}^2/\text{s}$  at  $40 \text{ }^\circ\text{C}$ .**Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Contains zinc oxide which is an acute and chronic category 1 solid (non-biodegradable, minimal LC50 of 0.042 mg/L) that is harmful to the environment.

Based on available data, aluminum oxide is not classified as environmental hazard according to GHS criteria.

**Acute Ecotoxicity**

Category 1

Very toxic to aquatic life

**Chronic Ecotoxicity**

Category 1

Very toxic to aquatic life with long lasting effects.

Avoid release to the environment. Collect spillage.

**Biodegradability**

Not readily biodegradable

**Other Effects**

Not available

**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

**SUPER THERMAL GREASE II****8616****Section 14: Transport Information****Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations); **USA DOT 49 CFR** (Parts 100 to 185) **Regulations.**

Sizes under 450 kg

**NOT REGULATED** in TDG  
per Special Provisions 99*FOR REFERENCE ONLY***UN number:** UN3077**Shipping Name:**  
ENVIRONMENTALLY

Sizes 5 kg and under

**NOT REGULATED** in 49 CFR  
per exception 171.4 (c)(2)HAZARDOUS SUBSTANCE, SOLID,  
N.O.S. (zinc oxide)**Class:** 9**Packing Group:** III**Marine Pollutant:** Yes

**Special Provision 99 (2):** These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety.

*Section continued on the next page*

**SUPER THERMAL GREASE II**

**8616**

**Air**

**Refer to ICAO-IATA regulations.**

Sizes 5 kg and under

Cat. No. 8616-4G, 8616-3ML, 8616-25ML, 8616-85ML, 8616-1P

**NOT REGULATED**

On the air waybill, write  
"Not Restricted, as per  
Special Provisions A197"

Sizes over 5 kg

Cat. No. 8616-1G


**UN number:** UN3077

**Shipping Name:** ENVIRONMENTALLY  
HAZARDOUS SUBSTANCE, SOLID,  
N.O.S. (zinc oxide)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes



**Special Provision A197:** These substances when transported in single or combination packagings containing net quantity per single or inner packaging of less than 5 L or less for liquids or having a net mass of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

**Sea**

**Refer to IMDG regulations.**

Sizes 5 kg and under

Cat. No. 8616-4G, 8616-3ML, 8616-25ML, 8616-85ML, 8616-1P

**NOT REGULATED**

per 2.10.2.7

Sizes over 5 kg

Cat. No. 8616-1G


**UN number:** UN3077

**Shipping Name:** ENVIRONMENTALLY  
HAZARDOUS SUBSTANCE, SOLID,  
N.O.S. (zinc oxide)

**Class:** 9

**Packing Group:** III

**Marine Pollutant:** Yes



**2.10.2.7:** Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provision of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of this Code relevant to any additional hazards continue to apply.

**Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.**

**SUPER THERMAL GREASE II**

**8616**

**Section 15: Regulatory Information**

**Canada**

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)**

All hazardous ingredients are listed on the DSL/NDSL.

**Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


**USA**

**Other Classifications**

**HMIS® RATING**

<b>HEALTH:</b>	<b>1</b>
<b>FLAMMABILITY:</b>	<b>1</b>
<b>PHYSICAL HAZARD:</b>	<b>0</b>
<b>PERSONAL PROTECTION:</b>	

**NFPA® 704 CODES**



*Approximate HMIS and NFPA Risk Ratings Legend:*

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

**CAA** (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

**EPCRA** (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains aluminum oxide (CAS# 1344-28-1) and zinc compounds (CAS# 1314-13-2) which can be subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372 under certain conditions.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

*Section continued on the next page*

**SUPER THERMAL GREASE II****8616**

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, June 06, 2014 revision, USA 2, 2011 revision, USA).

This product does not contain any listed substances in California.

**Europe****RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, or PBDE's, and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

**Section 16: Other Information**

<b>SDS Prepared by</b>	Michel Hachey
<b>Date of Revision</b>	20 June 2017
<b>Supersedes</b>	11 May 2017
<b>Reason for Changes:</b>	Revision to section 12

**Reference**

- 1) ACGIH 2013 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2013).
- 2) All toxicological data were checked against the RTECS (Registry of Toxic Effects of Chemical Substances®)

**Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
PPE	Personal Protection Equipment
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

*Section continued on the next page*

**SUPER THERMAL GREASE II****8616**

**Technical Queries** Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at [www.mgchemicals.com](http://www.mgchemicals.com).

Email: [support@mgchemicals.com](mailto:support@mgchemicals.com)

**Mailing Addresses** *Manufacturing & Support*  
1210 Corporate Drive  
Burlington, Ontario, Canada  
L7L 5R6

*Head Office*  
9347-193rd Street  
Surrey, British Columbia, Canada  
V4N 4E7

**Disclaimer** This material safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.