

Capture

Product Spec Sheet
R2-2MPHDMOEY

2MP HDCVI IR MOTORIZED EYEBALL

Multi Format: CVI, CVBS, AHD,
TVI



The R2-2MPHDMOEY HDCVI eyeball camera is constructed with a 2.7~12mm motorized lens. This 2MP camera is IP67 rated and uses existing cabling infrastructure for a default HDCVI signal with a switchable output option to other multi formats (AHD, TVI, CVBS). The multi-language OSD provides structural flexibility and high performance making this camera an ideal choice for numerous indoor/outdoor applications such as commercial applications, home or office use as well as monitoring hallways, unattended storage areas & various other installation applications

FEATURES

- 1/2.7"CMOS, 2MP
- 0.02LUX/F1.7, 0LUX IR ON
- 30FPS@1080P
- CVI/CVBS/AHD/TVI SWITCHABLE
- 2.7~12MM, MOTORIZED VARI-FOCAL LENS
- MAX. IR LENGTH 60M (197FT), SMART IR
- IP67, DC12V
- WARRANTY: 36 MONTHS
- R2-2MPHDMOEY
- UPC: 840049303478
- MASTER CARTON UPC: 10840049303475
- WEIGHT: 1.59 LB
- UNIT DIMENSIONS: Φ 4.80"X4.13"



MADE
IN China

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON

Capture

Product Spec Sheet
R2-2MPHDMOEY

CAMÉRA SPHÉRIQUE MOTORISÉE HDCVI IR 2 MPX

Formats multiples: CVI, CVBS, AHD, TVI



La caméra sphérique R2-2MPHDMOEY HDCVI est dotée d'un objectif motorisé de 2,7 à 11 mm. Cette caméra de 2 MPx est conforme à la norme IP67 et utilise l'infrastructure de câblage existante pour un signal HDCVI par défaut avec une option de sortie commutable vers d'autres formats multiples (AHD, TVI, CVBS). L'OSD multilingue offre une flexibilité structurelle et des performances élevées qui font de cette caméra un choix idéal pour de nombreuses applications intérieures/extérieures, comme les applications commerciales, l'utilisation à domicile ou au bureau ainsi que la surveillance des couloirs, des aires de stockage sans surveillance et diverses autres applications d'installation.

FEATURES

- CMOS 1/2,7 PO, 2 MPX
- 0,02 LUX/F1,7, 0 LUX IR ACT.
- 30 I/S À 1080P
- COMMUTABLE CVI/CVBS/AHD/TVI
- OBJECTIF VARIFOCAL DE 2,7 À 12 MM
- PORTÉE MAXIMALE IR DE 60 M, SMART IR
- IP67, 12 VCC
- GARANTIE: 36 MOIS
- R2-2MPHDMOEY
- UPC: 840049303478
- MASTER CARTON UPC: 10840049303475
- WEIGHT: 1.59 LB
- UNIT DIMENSIONS: Φ4.80"X4.13"



MADE
IN China

FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON

R2-2MPHDMOEY	
TECHNICAL SPECIFICATION	
CAMERA	
IMAGE SENSOR	1/2.7" CMOS
EFFECTIVE PIXELS	1920(H) X 1080(V), 2MP
SCANNING SYSTEM	PROGRESSIVE
ELECTRONIC SHUTTER SPEED	PAL: 1/25-1/1000000S NTSC: 1/30-1/1000000S
MINIMUM ILLUMINATION	0.02LUX/F1.7, 30IRE, 0LUX IR ON
S/N RATIO	MORE THAN 65DB
IR DISTANCE	UP TO 60M (197FT)
IR ON/OFF CONTROL	AUTO / MANUAL
LENS	
LENS TYPE	MOTORIZED VARI-FOCAL
MOUNT TYPE	Φ14
FOCAL LENGTH	2.7 MM-12 MM
MAX APERTURE	F1.7
ANGLE OF VIEW	DIAGONAL: 38°- 125° HORIZONTAL: 33°-102° VERTICAL: 19°- 53°
IRIS TYPE	FIXED IRIS
CLOSE FOCUS DISTANCE	12 M (3.9 FT)
VIDEO	
RESOLUTION	1080P (1920 X 1080)
FRAME RATE	25/30FPS@1080P, 25/30/50/60FPS@720P
VIDEO OUTPUT	1-CHANNEL BNC HIGH DEFINITION VIDEO OUTPUT / CVBS VIDEO OUTPUT (CHOICES OF CVI/TVI/AHD/CVBS)
DAY/NIGHT	AUTO (ICR) / MANUAL
OSD MENU	MULTI-LANGUAGE
BLC MODE	BLC / HLC / DWDR
WDR	DWDR
GAIN CONTROL	AGC
NOISE REDUCTION	2D
WHITE BALANCE	AUTO / MANUAL
SMART IR	AUTO / MANUAL
INTERFACE	
AUDIO INTERFACE	ONE CHANNEL BUILT-IN MIC (-A)
ELECTRICAL	
POWER SUPPLY	12V DC ±30%
POWER CONSUMPTION	MAX. 2.7W (12V DC, IR ON)
ENVIRONMENTAL	
OPERATING CONDITIONS	-30°C TO +60°C (-22°F TO 140°F);<95% (NONCONDENSATION)
INGRESS PROTECTION & VANDAL RESISTANCE	IP67
CONSTRUCTION	
DIMENSIONS	Φ122MM X 104.8MM (Φ4.80" X 4.13")
NET WEIGHT	0.57 KG (1.26 LB)
GROSS WEIGHT	0.72 KG (1.59 LB)